

Matte-touch resin

Y582

Product Introduction:

Y582 is a clean resin with high hardness, high wear resistance, easy dulling properties, and good wettability. It is especially suitable for matte film printing, wood UV coatings, and plastic UV coatings..

Product Features:

- ◆ High hardness
- ◆ Wear resistance
- ◆ Good wettability

Application

- ◆ Matte film printing, wood UV paint and plastic UV paint

Specification

200 KG/drum

Technical information

Chemical composition	Polyurethane acrylate
Active content	100%
Appearance	Transparent liquid
Viscosity (mPa·s, 25℃)	20-50
Functionality	4

Taboo

- ◆ Slight irritation to skin and eyes. Wash with soap and plenty of water immediately after contact. In severe cases, seek medical attention immediately.

Storage and shelf life

- ◆ Transportation and storage of non-hazardous chemicals
- ◆ Cool, dry and sealed storage
- ◆ Shelf life: 12 months from the date of production

This information and all further technical suggestions are based on our existing knowledge and experience. However, such information and technical advice do not mean that we should bear any debts or other legal responsibilities, including those related to existing third-party intellectual property rights, especially patent rights. In particular, we have no intention to make or imply any legal guarantee or guarantee on product attributes. We reserve the right to make any changes based on technical progress or further development. Customers are still obliged to carefully inspect and test the products they buy. The performance of the products mentioned in this statement shall be determined by tests, which shall be conducted only by qualified experts and independently by customers. Quoting trade names used by other companies does not mean recommending any products, nor does it imply that similar products cannot be used.

Guangdong Aosite New Materials Co., Ltd.
<https://uvsilicone.com/>

