

Polyurethane acrylate

YM110

Product Introduction:

YM110 is a bifunctional polyurethane acrylate resin. It features low Tg, low odor, high elongation, good adhesion, and good weather resistance. It can be applied to adhesives, coatings, inks, etc.

Product Features:

- ◆ Low Tg
- ◆ Good adhesion
- ◆ Good weather resistance

Application

- ◆ Adhesives, coatings, inks, etc.

Specification

200 KG/drum

Technical information

Chemical composition	Polyurethane acrylate
Active content	100%
Appearance	Light yellow transparent liquid
Color (Gardner)	≤2
Viscosity (CPS/60℃)	6500-20000
Functionality	2

Taboo

- ◆ Avoid touching skin, eyes and clothes, and wear protective gloves when operating.
- ◆ Wipe it clean with a cloth and clean it with ethyl acetate when it leaks.

Storage and shelf life

- ◆ Transportation and storage of non-hazardous chemicals
- ◆ Cool, dry and sealed storage, the storage temperature shall not exceed 40℃, and it shall be protected from sunlight
- ◆ Being close to the heat source will cause uncontrollable polymerization and give off a lot of heat.
- ◆ Shelf life: 12 months from the date of production

This information and all further technical suggestions are based on our existing knowledge and experience. However, such information and technical advice do not mean that we should bear any debts or other legal responsibilities, including those related to existing third-party intellectual property rights, especially patent rights. In particular, we have no intention to make or imply any legal guarantee or guarantee on product attributes. We reserve the right to make any changes based on technical progress or further development. Customers are still obliged to carefully inspect and test the products they buy. The performance of the products mentioned in this statement shall be determined by tests, which shall be conducted only by qualified experts and independently by customers. Quoting trade names used by other companies does not mean recommending any products, nor does it imply that similar products cannot be used.

Guangdong Aosite New Materials Co., Ltd.
<https://uvsilicone.com/>

