


N-Dimethylacrylamide

DMMA

Product Introduction:



Product Features:

- ◆ Low viscosity
- ◆ Strong solvency
- ◆ Fast curing speed
- ◆ Excellent substrate adhesion

Applicability

Water-base

●

Solvent-less

●

Paint

◎

Solvent-base

●

Bicomponent

◎

Varnish

◎

○ Unsited ◎ Partially suited ● Suited

Application

- ◆ UV adhesives
- ◆ UV

Technical information

Chemical composition

Color (APHA)	≤100
Appearance	Colorless or slightly yellow liquid
Viscosity (mPa s, 25℃)	1-5
Water content (Karl Fischer, %)	≤0.1
Density (20 °C g/cm3)	
Surface tension (mN/m, 25℃)	
Refractive index (25℃)	

Solubility

Recommended addition

Chemical usage process

Manner of packing

200kg/drum

Storage and shelf life

- ◆ Store in a cool and dry place, avoid direct sunlight.
- ◆ Avoid direct contact with skin and eyes.
- ◆ Keep away from oxidants and free radical compounds.

This information and all further technical suggestions are based on our existing knowledge and experience. However, such information and technical advice do not mean that we should bear any debts or other legal responsibilities, including those related to existing third-party intellectual property rights, especially patent rights. In particular, we have no intention to make or imply any legal guarantee or guarantee on product attributes. We reserve the right to make any changes based on technical progress or further development. Customers are still obliged to carefully inspect and test the products they buy. The performance of the products mentioned in this statement shall be determined by tests, which shall be conducted only by qualified experts and independently by customers. Quoting trade names used by other companies does not mean recommending any products, nor does it imply that similar products cannot be used.

公司名称加网:Guangdong Aosite New Materials Co., Ltd.

<https://uvsilicone.com/>

公司logo

