

Monomer

OXEA

Product Features:

- ◆ low viscosity
- ◆ Low volatility
- ◆ Low glass transition temperature
- ◆ Good weather resistance
- ◆ low shrinkage
- ◆ Flexibility
- ◆ Good water resistance

Application

- ◆ UV glue
- ◆ Resin thickener
- ◆ Synthetic resin raw materials
- ◆ Waterborne UV Resin Raw Materials
- ◆ Printing ink thinner

Technical information

| | |
|--|---|
| Chemical Name | 2-(2-oxo-1,3-oxazinyl-3-yl)ethanol acrylate |
| Appearance | Pale yellow transparent liquid |
| Polymerization Inhibitor (MEHQ) (ppm) | <400 |
| Acid Value (mg KOH/g) | ≤1 |
| Color | ≤200 |
| Viscosity (mPa·s, 25°C) | 28±5 |

Specification

Net weight 200Kg/drum

Storage

- ◆ Transportation and storage of non-hazardous chemicals
- ◆ Cool, dry and sealed storage

This information and all further technical suggestions are based on our existing knowledge and experience. However, such information and technical advice do not mean that we should bear any debts or other legal responsibilities, including those related to existing third-party intellectual property rights, especially patent rights. In particular, we have no intention to make or imply any legal guarantee or guarantee on product attributes. We reserve the right to make any changes based on technical progress or further development. Customers are still obliged to carefully inspect and test the products they buy. The performance of the products mentioned in this statement shall be determined by tests, which shall be conducted only by qualified experts and independently by customers. Quoting trade names used by other companies does not mean recommending any products, nor does it imply that similar products cannot be used.

Guangdong Aosite New Materials Co., Ltd.
<https://uvsilicone.com/>

